





WAV-0110 Wireless Outdoor Sensor


Dip Switch Settings




Dip 1 ON only: 500 Ohms



Dip 2 ON only: 5k Ohms



Both ON: 12 - 20k Ohms



Both OFF : 10k Ohms*
*Default Setting

Supported Product Examples

Setting	Boiler Model	Control Model
5K	<ul style="list-style-type: none"> • Viessmann Vitodens- 100W 	<ul style="list-style-type: none"> • Heat Timer (excluding EPU-CH)
10K	<ul style="list-style-type: none"> • Laars Mascot • Laars Neotherm • Viessmann (excluding Vitodens-100W) • Lochinvar • Camus • ATH • Navien • Buderus GB Series • Allied SG, AAA & Electric • IBC SL, VFC • Slant/Fin CHS • NTI Trinity & Vmax • Raypak • RBI • Smith Boiler 	<ul style="list-style-type: none"> • Honeywell AQ2000 • Uponor CCN • Taco iWorx • HBX Controls
12K	<ul style="list-style-type: none"> • Peerless Purefire • IBC DC & HC Series • Triangle Tube Prestige Solo & ACVMax • HTP Elite • Allied HSE • Bosch Greenstar • Weil-McLain Ultra Series 3, Evergreen & 97+ • Slant/Fin Lynx • Slant/Fin Jaguar 	
20K		<ul style="list-style-type: none"> • Honeywell Building Controls

Contact Information

4516-112th Avenue SE
Calgary, Alberta T2C 2K2
CANADA

Phone: +1 (403) 720 0029
Fax: +1 (403) 720 0054
Email: info@hbxcontrols.com