

MC3+

RAPIDE

Central Heating System CLEANER

High performance *MC3+ RAPIDE* from ADEY, the makers of the market leading *MagnaClean*® filter, removes both system corrosion and limescale deposition. *MC3+ RAPIDE* provides faster, stronger and easier dosing; allowing a 125 litre system to be dosed in just 20 seconds.

MC3+ RAPIDE central heating system cleaner is a new rapid performing and powerful chemical cleaner specially designed to remove central heating system sludge and debris. Formulated to provide better sludge removal for the average-sized system AND cleans systems with up to 15 radiators.

The latest *MC3+ RAPIDE* chemical is the product of a considerable amount of industry knowledge and experience built up over a long number of years. It has been developed and tested within ADEY's own UKAS accredited laboratories here in the UK.

- High performance chemical cleaner
- Removes sludge, debris and scale
- Restores heating efficiency of existing systems
- Treats 125 litre system in 20 seconds
- For use in accordance with BS7593:2006
- Suitable for all heating systems and all water types
- Compatible with all metals including aluminium

Physical and chemical properties

Appearance:	Liquid
Colour:	Brown
Odour:	Slight
Solubility:	Soluble in water
pH (concentrated solution):	7.0
Relative Density:	1.18 g/cm ³

Product uses

For the removal of system sludge, debris and scale from existing heating systems, restoring heating efficiency. Removes corrosion from all metals and alloys commonly found in heating systems including mild steel, copper, aluminium and their alloys. Compatible with all rubbers and other non-metallic components.

How to use

300ml of *MC3+ RAPIDE* treats up to 125 litres or 15 single panel radiators

Introduce *MC3+ RAPIDE* to the system using the adaptor provided via the filling loop, radiator or through a *MagnaClean* filter air vent.

Clean system as recommended in BS7593 using ADEY *MagnaCleanse* and *MC3+ RAPIDE*. For heavily sludged systems, ADEY *MC5 RapidFlush System Cleaner* is recommended. Following the cleanse, drain and flush thoroughly until the water runs clear. Refill the system and add the correct dosage of *MC1+* for the optimum protection against the build-up of corrosion and limescale.

Application

MC3+ RAPIDE is suitable for all sealed and open vented central heating systems in accordance with BS7593. *MC3+ RAPIDE* is not suitable for use in single feed indirect "primatic" cylinders where potable water treatment is required.

Packaging, handling and storage

Available in 300ml canister. *MC3+ RAPIDE* is non-hazardous, but as for all domestic chemicals, keep out of reach of children. Warning: Pressurised container: May burst if heating. Protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep out of reach of children. Use only as directed.



MO2620