

Futera II Series Submittal Data

JOB NAME: LOCATION:			
		ARCH/ENGR:	
CONTRACTOR: MODEL NO: TYPE GAS: BTU INPUT/OUTPUT: ADDITIONAL INFORMATION:			
		Standard Features	Optional Equipment
		• 85% Efficiency	☐ Propane Gas
		• Cast Iron Headers (Boilers)	☐ Cupronickel Heat Exchanger
		• Bronze Headers (Water Heaters)	☐ Wired & Mounted Flange
 Sealed Combustion 	☐ 5' Pump Pigtail		
• 2 Stage Digital Operator	☐ Alarm Bell		
 Self Diagnostic Control 	☐ Flame Failure Dry Contact		
• Low NO _x	☐ Main Flame Status Relay		
 Proven Pilot (UV Flame Detection) 	☐ Enable/Disable Relay 24V		
 Finned Copper Tube Heat Exchanger 	☐ Enable/Disable Relay 120V		
Gasket-less Heat Exchanger Assembly	☐ Low Gas Pressure Switch		
 High Strength Low Alloy Steel Burner 	☐ High Gas Pressure Switch		
 ASME Pressure Relief Valve Mounted 	☐ C.A.D. Dry Contact		
• 20 Amp Pump Contactor Single Phase	☐ Freeze Protection Kit		
Flame Safeguard Control	☐ Stainless Steel Jacket		
 Low Air Pressure Switch 	□ Power Venting Wiring		
Pump Delay Control	☐ Three Phase Pump Contactor		
Stainless Steel Combustion Chamber	☐ Keyboard Display Module		
Heat Exchanger Drain Valves	☐ Remote/Local Switch		
• Temperature/Pressure Gauge (Boilers)	☐ Sidewall Vent Kit		
Flow Switch Mounted and Wired	☐ Sidewall Vent Kit w/Air Intake Hood		
Manual Reset High Limit	□ Vent Termination Hood		
• Intake Air Filter	☐ Air Intake Hood		
• FM/CSD-1 Compliant Gas Train	☐ Barometric Damper		
Compact, Low Maintenance Design	Outdoor Installation		
Easy Access to all Components	\square Pump		
Venting Flexibility	Occ Trains		
National Board Certified Control of the Indianal	Gas Trains ☐ CSD-1 Code		
CSA Design Certified and Listed	□ CSD-1 Code		

☐ Kentucky Code

SCAQMD Rule 1146.2