


Submittal Data Sheet

Wilo SCP – Horizontal Split Case Pumps



SCP 4 x 3 x 9 HA



Project:

Engineer:

Contractor:


Submitted By:

Date:

Approved By:

Date:

Tag #	Model #	Flow (USGPM)	Head (Feet)	HP	Enclosure TEFC/ODP	Frame	Cycle	Phase	Voltage	RPM
	SCP 4 x 3 x 9 HA						60 Hz	3		



Technical Data

Approved Fluids

Heating Water

Cooling and cold water

Water-Glycol mixtures (for 20–40% glycol and fluid temp ≤ 104°F [40°C])

Fluid Temperature

Mechanical Seal 18°F to 250°F (–8°C to 120°C)

Stuffing Box Packing 18°F to 220°F (–8°C to 105°C)

Materials of Construction

American Standard


<input type="checkbox"/> Pump Housing	A48 Class 35
<input type="checkbox"/> Pump Housing (Optional)	Ni-resist BS 3468 Gr 2 / BS 2789 500.1
<input type="checkbox"/> Impeller	BS 84 C83 600
<input type="checkbox"/> Impeller (optional)	A48 Class 35 / BS 84 C83 600
<input type="checkbox"/> Stationary Wear Rings	BS 84 C93 700
<input type="checkbox"/> Pump Shaft	A276 type 410
<input type="checkbox"/> Pump Shaft (optional)	BS 970 316 S16
<input type="checkbox"/> Mechanical Seal	Carbon/silicon carbide/EPDM (E1)
<input type="checkbox"/> Other Mechanical Seals	Avail. on request
<input type="checkbox"/> Additional Spacer Coupling	Avail. on request
<input type="checkbox"/> Other:	

Approval Stamp

Wilo SCP – Horizontal Split Case Pumps



Single Stage Pump



Dimensions – Inches (mm)

Frame	a	L	I	L1	L2	L3	L4	LM	LP	H1	H2	HO	Ht	n	Ød	S1	S2	S3	S4	S5	SL	P5	P6
184T	.50 (13)	46.38 (1178)	16.31 (414)	13.63 (346)	15.69 (398)	8.88 (226)	7.50 (191)	16.56 (421)	29.38 (746)	9.81 (249)	6.50 (165)	21.00 (533)	8.75 (222)	4	.81 (21)	1.31 (33)	4.00 (102)	29.00 (737)	10.50 (267)	11.90 (302)	37.00 (940)	-	-
	.50 (13)	47.75 (1213)	16.31 (414)	13.63 (346)	15.69 (398)	8.88 (226)	7.50 (191)	17.88 (454)	29.38 (746)	9.81 (249)	6.50 (165)	21.00 (533)	8.75 (222)		4	.81 (21)	1.31 (33)	4.00 (102)	29.00 (737)	10.50 (267)	11.90 (302)	37.00 (940)	-
213T	.50 (13)	48.88 (1242)	16.31 (414)	13.63 (346)	15.69 (398)	8.88 (226)	7.50 (191)	19.00 (483)	29.38 (746)	9.81 (249)	6.50 (165)	21.00 (533)	8.75 (222)	4		.81 (21)	1.31 (33)	4.00 (102)	29.00 (737)	10.50 (267)	11.90 (302)	37.00 (940)	-
	.50 (13)	48.88 (1242)	16.31 (414)	13.63 (346)	15.69 (398)	8.88 (226)	7.50 (191)	19.00 (483)	29.38 (746)	9.81 (249)	6.50 (165)	21.00 (533)	8.75 (222)		4	.81 (21)	1.31 (33)	4.00 (102)	29.00 (737)	10.50 (267)	11.90 (302)	37.00 (940)	-
215T	.50 (13)	48.88 (1242)	16.31 (414)	13.63 (346)	15.69 (398)	8.88 (226)	7.50 (191)	19.00 (483)	29.38 (746)	9.81 (249)	6.50 (165)	21.00 (533)	8.75 (222)	4		.81 (21)	1.31 (33)	4.00 (102)	29.00 (737)	10.50 (267)	11.90 (302)	37.00 (940)	-
	.50 (13)	48.88 (1242)	16.31 (414)	13.63 (346)	15.69 (398)	8.88 (226)	7.50 (191)	19.00 (483)	29.38 (746)	9.81 (249)	6.50 (165)	21.00 (533)	8.75 (222)		4	.81 (21)	1.31 (33)	4.00 (102)	29.00 (737)	10.50 (267)	11.90 (302)	37.00 (940)	-

Dimensions – Inches (mm)

DN S #125	ØD	Ød	Øk	b	n	D2
4	9.00 (229)	6.19 (157)	7.50 (191)	.94 (24)	8	.75 (19)

Dimensions – Inches (mm)

DN D 125#	ØD	Ød	Øk	b	n	D2
3	7.50 (191)	5.50 (140)	6.00 (152)	.94 (24)	4	.75 (19)

